

## RHCE-NP



- Water proof rating: IP68 (for underground un-pressurised telecom network)
- Cable entry and sealing: through sides of closure. Sealing achieved through flame being applied to heat shrink material.
- Capacity: Multiple capacities offered – up to 3600 pairs
- Operation:
  - Heat-shrinkable joint closure
  - Excellent mechanical and environmental protects joints in the unpressurised access network: aerial, buried or ducted, on filled or jelly filled, with polyethylene, lead, steel or aluminium sheaths.
- Metal canister protects the splice bundle
- Excellent environmental and mechanical characteristics
- Branch kits are available

### PRODUCT DIMENSIONS – RHCE-NP Series

Product Code	Splice Bundle Diameter (D) (mm)	Cable Diameter (d) (mm)	Max Joint Gap (L) (mm)	Sleeve Length (S) (mm)
500-43/8-200	43	8	200	445
500-43/8-350	43	8	350	600
500-43/8-500	43	8	500	755
500-75/15-250	75	15	250	505
500-75/15-500	75	15	500	710
500-75/15-650	75	15	650	860
500-92/25-300	92	25	300	665
500-92/25-500	92	25	500	830
500-92/25-600	92	25	600	985
500-122/30-300	122	30	300	680
500-122/30-500	122	30	500	860
500-122/30-650	122	30	650	1010
500-160/42-500	160	42	500	920
500-160/42-720	160	42	720	1100
500-200/50-500	200	50	500	940
500-200/50-720	200	50	720	1120

REPL reserve the right to update the information contained in this document at any time without notice. It is the users responsibility to ensure it is suitable for the intended application. Any implied warranty relating to fitness for a particular purpose are explicitly excluded unless agreed in writing by REPL.

©REPL 2017